



**"S" Series Stand-alone Valve Modules Model Number Index**  
**Complete Modules (Complete with Pneumatic and Electrical Connectors)**

**A**

**BOLD OPTIONS ARE STANDARD**

**P2M 1 S 4ES 2C 00 A F4**

Basic Series	
Moduflex	P2M

Size	
Size 1	1
Size 2	2

Valve Series	
Stand Alone	S

Valve Type / Function	
<b>3-Way / 2-Position</b>	
Single Solenoid, NC Spring Return	3ES
Single Air Pilot, NC Spring Return	3PS
<b>4-Way / 2-Position</b>	
Single Solenoid, Spring Return	4ES
Single Air Pilot, Spring Return	4PS
Double Solenoid	4EE
Double Air Pilot	4PP
<b>Dual 3-Way, 2-Position, Spring Return</b>	
Solenoid, NC / NC + PO Check (4/3 APB)	BEE*
Air Pilot, NC / NC + PO Check (4/3 APB)	BPP*
Solenoid, NO / NO (4/3 Pressure Ctr.)	CEE
Air Pilot NO / NO (4/3 Pressure Ctr.)	CPP
Solenoid, NC / NC with Exhaust Check	DEE
Air Pilot, NC / NC with Exhaust Check	DPP
Solenoid, NO / NC with Exhaust Check	EEE
Solenoid, NC / NC without Check (4/3 Exh. Ctr.)	GEE

\*Valve includes peripheral P. O. Check Valve and union fittings.

Operator Voltage	
24VDC	2C
Remote Pilot - 5/32" (4mm) Tube	00

Ports (All Ports)	
C0*	10mm Elbow Fitting
C2*	12mm Elbow Fitting
<b>C4</b>	<b>5/32" (4mm) Elbow Fitting</b>
C6	6mm Elbow Fitting
<b>C7</b>	<b>1/4" Elbow Fitting</b>
C8*	8mm Elbow Fitting
<b>C9*</b>	<b>3/8" Elbow Fitting</b>
F0*	10mm Straight Fitting
F2*	12mm Straight Fitting
<b>F3*</b>	<b>1/2" Straight Fitting</b>
<b>F4</b>	<b>5/32" (4mm) Straight Fitting</b>
F6	6mm Straight Fitting
<b>F7</b>	<b>1/4" Straight Fitting</b>
F8*	8mm Straight Fitting
<b>F9*</b>	<b>3/8" Straight Fitting</b>

\* Only Available with Size 2 Valves.

Fitting Configuration	
<b>A*</b>	<b>Straight Fittings</b>
<b>B*</b>	<b>Elbow Fittings</b>
<b>C**</b>	<b>Straight Fitting &amp; Muffler</b>
<b>D**</b>	<b>Elbow Fitting &amp; Muffler</b>

\* Ports 1 & 3 fittings sizes are same as Ports 2 & 4 (See example at left.)

† Fitting in Port 1, Muffler in Port 3

LED / Cable	
<b>00</b>	<b>No Cable, No LED, No Surge Suppression</b>
<b>V2</b>	<b>2 Meter Cable with LED and Surge Suppression</b>
<b>V5</b>	<b>5 Meter Cable with LED and Surge Suppression</b>
<b>V9</b>	<b>9 Meter Cable with LED and Surge Suppression</b>

**EXAMPLE for Fitting Configuration:**  
**Size 1**

**CF7** Ports 1 & 3  
 1/4" Straight Fitting & Muffler  
 Ports 2 & 4  
 1/4" Straight Fittings

**Size 2**

**AC0** Ports 1 & 3  
 10mm Elbow Fittings  
 Ports 2 & 4  
 10mm Elbow Fittings

**With Only One Universal Solenoid Pilot for all Configurations**

24VDC is now a global standard for all machines.

The Moduflex 24VDC unique solenoid pilot is supplied with the multi-function manual override that can be adapted to all requirements, as explained by the drawings.

**Multi-Function Adaptable Manual Override**

